

# Expected Pump Performance Curve & Specifications (Reference)

**Pump model : NH-200PS-F (M)**

REF : A3400150

Frequency : 50/60 Hz

IMPELLER DIA : mm

## Pump specifications

- 1). Specified point : 5.0m at 40.0 L/Min
- 2). Max Head – Discharge flow : 6.5m – 60.0 L/Min
- 3). Hose : H, Thread : T, Flange : F  
 Discharge 26mm, NPT 1 inch, 25A Flange  
 Suction 26mm, NPT 1 inch, 25A Flange
- 4). Permissible working Temp. : 0 ~ 90°C , Carbon fiber filled ETFE
- 5). Permissible system pressure : 2.4 Bar
- 6). Permissible environment conditions : 0 ~ 40°C , Upto 85%
- 7). Nominal speed : 2,700 / 3,300 r.p.m.
- 8). Allowable S. G. : 1.5

## Motor specifications

- 1). Nominal output \* input : 150 \* 290Watts
- 2). Applicable voltage : 100~120V 50,60Hz    200~240V 50,60Hz  
 : 200/400V 50,60Hz    220/380V 50,60Hz  
 : 220/440V 60Hz
- 3). Insulation grade : E grade
- 4). Single phase capacitor motor  
 3 Phase Original Motor  
 3 Phase IEC Motor

